



>THIS IS THE WAY

>THIS IS NORTEL™

Product Bulletin

Nortel Norstar Modular ICS

Technical Specifications

Service tone cadences

Tone	Cadence (seconds)
Busy	0.5 on/0.5 off
Expensive route	0.3 on/0.3 off (3 bursts)
Overflow	0.25 on/0.25 off
Ringback	2.0 on/4.0 off
Confirmation	1.0 on/1.0 off (3 bursts followed by no tone)
Recall	1.0 on/1.0 off (3 bursts followed by steady tone)
Ring splash	0.2 on (1 burst)

Power specifications

Characteristic	ICS	TM	SM
Voltage V ac	110 - 120	110 - 120	110 - 120
Current A rms (max)	2.6	1.75	1.0
Frequency Hz	47 - 63	45 - 70	45 - 70
Crest factor	4.0	4.0	4.0

Telephone loop specifications

Characteristic	Value
Loop resistance	64 Ohms (300 m of 0.5 mm wire or 1000 ft. of 24 AWG wire)
Loop length	300 m (1000 ft.) without SAPS 780 m (2600 ft.) with SAPS
Minimum voltage at telephone	10 V dc
Current at telephone (idle)	45 mA nominal
Current at telephone (active)	80 mA maximum

Electrical requirements

Characteristic	Spec/value
Electrostatic discharge	
ICS and telephones	IEC 1000-4-2 / EN 61000-4-2 severity level 3 maximum of 15 kV with a 300 Ohm/150 pF probe
Connectors	IEC 1000-4-2/EN 61000-4-2 severity level 2
Radiated immunity	Maximum of 5 V/m from 100 kHz to 1 GHz
Conducted immunity	Maximum of 3 V rms from 0.1 MHz to 30 MHz

Digital trunk interface/network interface

Characteristic	Spec/value
Physical	RJ48C 8-pin modular jack
Line rate	1.544 +/- 32 Mbps
Framing	Superframe/extended superframe*
Line code	AMI/B8ZS*
Impedance	100 Ohms

DSX1 operation

Characteristic	Spec/value
Pre-equalization	0 - 700 ft.*
Stratum	4E

CSU operation	
Characteristic	Spec/value
Line build out	0, 7.5, or 15 dB*
Input dynamic range	0 to -26 dB (typical)
Performance reporting	Simultaneous support of TR 54016 or TIA-547A
Line loopback support	Remote activation/deactivation via in-band code or FDL as per TR 54016 or TIA-547A
Payload loopback support	Remote activation/deactivation via FDL as per TR 54016 or TIA-547A
Carrier failure alarms (CFA)	Alarm indication signal (AIS) Red Yellow

Trunk signaling support	
Characteristic	Spec/value
Loop start with answer and disconnect super.	OSI interval* Pulse/DTMF dialing*
DID	Immediate start (pulse dialing only), Wink start or Delay start,* Pulse/DTMF dialing*
E&M	Immediate start (pulse dialing only), Wink start, Delay start or ring-down tie line,* Pulse/DTMF dialing*

Local test support	
Characteristic	Spec/value
Monitor jack	Bridging via Bantam jack
Line loopback	Activate/deactivate via maintenance*
Payload loopback	Activate/deactivate via maintenance*
Card edge loopback	Activate/deactivate via maintenance
Continuity loopback	Activate/deactivate via push button on faceplate*

Physical specifications	
Characteristic	Spec/value
Height	24.8 in.
Width	11.8 in.
Depth	6.7 in.
Weight	13.23 lbs. with power supply 16.5 lbs. with all slots filled

* Value is set in configuration programming.



This is the Way. This is Nortel, Nortel, the Nortel logo, the Globemark and Norstar are trademarks of Nortel Networks. All other trademarks are the property of their owners.

Copyright © 2005 Nortel Networks. All rights reserved. Information in this document is subject to change without notice. Nortel assumes no responsibility for any errors that may appear in this document.

